

grandMA2 ultra-light

Art.-No. 120113



The grandMA2 ultra-light features the full network performance of the grandMA2 series. All controls are at the same place as on the on bigger consoles.

With its 4,096 parameters and 6 DMX outputs the grandMA2 ultra-light is the perfect backup solution too. It brings all the features of the series 2 consoles to smaller shows and budgets, including intuitive and fast control of all lighting genres and the handling of an almost infinite number of presets, cues, pages, sequences and effects.

All grandMA2 consoles are optionally available as Silent Version with optimised fan for noise-sensitive environments.

Features

- Real-time control for up to 65,536 parameters per session in connection with MA NPU (equivalent to 256 DMX universes)
- 4,096 HTP/LTP parameters
- 6 DMX outputs
- 1 internal TFT wide mode touchscreen (15.4" WXGA)
- 2 external TFT screens can be connected (UXGA, touchscreens accepted)
- 1 internal command screen – multi-touch (9" SVGA)
- 15 executor faders
- 2 etherCON connectors, 4 USB 2.0 connectors
- Motorized monitor wing
- 2 motorized A/B fader 100mm
- Individually backlit and dimmable silent (clickless) keys



Scope of delivery

Art.-No.	Article	Quantity
120122	MA LED desk light grandMA2, angle plug 90° XLR 4pin, length 27"	2
120132	Dust cover grandMA2 light and ultra-light	1

Technical Specifications

Operating voltage/ Supply voltage	120V/230V, 50/60Hz (automatic detection)
Power	350VA
Dimensions	935 x 204 x 652mm / 36.8 x 8 x 25.7inch
Net weight	30kg / 66.1lbs
Output connectors	6 x XLR 5pin (DMX) 2 x DVI (external monitor) 2 x etherCON 1 x MA Link (grandMA2 fader wing) 4 x USB 1 x DIN (MIDI) 2 x XLR 4pin (desklight)
Input connectors	1 x XLR 5pin (DMX) 1 x XLR 3pin (Sound) 1 x XLR 3pin (SMPTE) 1 x DIN (MIDI) 1 x Sub-D 25pol (Analogue Remote) 1 x powerCON

Article

Art.-No.	Article
120113	grandMA2 ultra-light

More product pictures

